

FineVu GX1100 4K		Remark
Image Sensor	8.46M pixels CMOS Image Sensor (1/2.8") 2M pixels CMOS Image Sensor (1/2.9")	
Resolution	3840×2160P (Ultra HD) 1920×1080P (Full HD)	
Frames Per Second	30fps	
Viewing Angle	Front: 136° Rear: 143°	Diagonal
Recording Mode	Driving Recording (Standard, Impact Detection, Time Lapse) Manual Recording Parking Recording (Motion Detection, Impact Detection, Time Lapse, Power Saving Parking)	
Display	Non-LCD	
Acceleration Sensor	3-axis acceleration sensor	+2g / -2g
GPS	Built-In	
Wi-Fi	Built-In(dongle)	
Storage Capacity	FineVu Micro SD Card (32GB ~ 128GB)	Class 10 or above, SDXC support
Battery	Super capacitor	
MIC	Built-In	
Speaker	Built-In	
Interface	Power port (3.5Ø), Rear camera port (2.5Ø), Button (REC/MIC, Wi-Fi), BT + Wi-Fi port (USB A Type), Micro SD card slot, Power switch	

FineVu GX1100 4K		Remark
Security LED	Front : White / Rear : White	
Input Power	DC 12V~24V	
Power Consumption	Parking Mode: 4.8W / Power Saving Parking Mode: 0.06W	2CH, GPS OFF / Wi-Fi OFF
High-Temperature Cut-Off	AI Heat Monitoring	During parking mode
Low Voltage Cut-Off	Supported	
Temperature	Operation: -20°C ~ 70°C (-4°F ~ 158°F) Storage: -30°C ~ 80°C (-22°F ~ 176°F)	
Size(WxDxH)	Front: 96.6 x 71.7 x 26.5mm (3.8 x 2.8 x 1.0") Rear: 46.8 x 29.9 x 36.5mm (1.8 x 1.1 x 1.4")	
Weight	Front: 123g (4.3oz) Rear: 28g (1.0oz)	
Language Supported	English, Chinese (Simplified, Traditional), French, German, Arabic, Hebrew, Italian, Japanese, Malay, Polish, Russian, Spanish, Thai, Turkish, Vietnamese, Korean	
Mobile Application	FineVu Cloud & Wi-Fi App	Android, iOS
PC Viewer	FineVu Player 2.0	Windows, MAC
Features	Auto Night Vision, AI Heat Monitoring, Power Saving Parking Mode, Time Lapse, ADAS PLUS (FVMA & LDWS), Speed Camera Alert, Low Voltage Cut-Off,	ADAS and Speed Camera Alert requires GPS reception
Certification	  	

